



FABBRICA CAVI - ANTENNE - ACCESSORI TV



# CW 0622.5

WARNING CABLE  
CEI-UNEL 36762 C-4 ( U<sub>o</sub> = 400 V )

Class CPR **E<sub>ca</sub>**

CU PLSF Pet-sp CU LAP/SP PLSF



A B C D E F

- A INNER CONDUCTOR** ..... PLAIN COPPER
- B INSULATION** ..... LOW SMOKE AND FUME POLYVINYL-CHLORIDE
- C NON-MIGRATING** ..... SPIRAL POLYESTER TAPE
- D DRAIN WIRE** ..... PLAIN COPPER
- E SHIELD** ..... SPIRAL ALUMINIUM + POLYESTER TAPE  
COVERAGE 100%
- F SHEATH** ..... LOW SMOKE AND FUME POLYVINYL-CHLORIDE

- PRINTING **SIVA CAVO ALLARME 2 X 0,50 + 6 X 0,22 CEI-UNEL 36762**  
**C-4 ( U<sub>o</sub> = 400 V ) MADE IN ITALY CE 62 SETT/ANNO**  
**EN 50575:2014 + A1:2016 Eca**

TEMPERATURE RANGE ..... -25°C / +80°C

## MECHANICAL DATA

|                  | CONSTRUCTION                            | SECTION                                              | SHEATH           | WEIGHT KG/KM<br>TOTAL |
|------------------|-----------------------------------------|------------------------------------------------------|------------------|-----------------------|
| <b>CW 0622.5</b> | 6 x (7 x 0,18 mm)<br>2 x (16 x 0,18 mm) | 6 x 0,22 mm <sup>2</sup><br>2 x 0,50 mm <sup>2</sup> | ø 5,20 ± 0,20 mm | bianco 9003<br>42,0   |

## ELECTRICAL PROPERTIES at 20°C

|                  | VOLTAGE   |        | CORES RESISTANCE     |                      | MIN. RESISTANCE<br>INSULATION |
|------------------|-----------|--------|----------------------|----------------------|-------------------------------|
|                  | OPERATING | TEST   | 0,22 mm <sup>2</sup> | 0,50 mm <sup>2</sup> |                               |
| <b>CW 0622.5</b> | 150 V     | 2000 V | 100 Ohm/Km           | 42 Ohm/Km            | 200 MOhm/Km                   |

The producer reserves himself to make modification on the item without any notice.