



FABBRICA CAVI - ANTENNE - ACCESSORI TV



AMC ...150

LOW TENSION HIGH RESISTANCE CABLE FOR GATE AUTOMATIONS
FIXED INSTALLATIONS IN HUMID AND NOT PROTECTED PLACES

CU

PVC

PVC

PUR



| A | B | C | D |

- A** INNER CONDUCTOR PLAIN COPPER
- B** INSULATION POLYVINYL-CHLORIDE
- C** SHEATH POLYVINYL-CHLORIDE
- COLOUR WHITE - RAL 9003
- D** SHEATH POLYURETHANE
- COLOUR GREEN - RAL 6018

TEMPERATURE RANGE -10 °C / +70 °C

MECHANICAL DATA

	SECTION	SHEATH		WEIGHT KG/KM TOTAL
AMC 2150	2 x 1,50 mm ²	ø 5,20 ± 0,20 mm	ø 7,20 ± 0,20 mm	79,2
AMC 3150	3 x 1,50 mm ²	ø 5,60 ± 0,20 mm	ø 7,60 ± 0,20 mm	97,0
AMC 4150	4 x 1,50 mm ²	ø 6,30 ± 0,20 mm	ø 8,30 ± 0,20 mm	120,6

ELECTRICAL PROPERTIES at 20°C

	VOLTAGE		CORES RESISTANCE
	OPERATING	TEST	
AMC 2150	450/750 V.	4000 V	12,0 Ohm/Km
AMC 3150	450/750 V.	4000 V	12,0 Ohm/Km
AMC 4150	450/750 V.	4000 V	12,0 Ohm/Km

The producer reserves himself to make modification on the item without any notice.