



FABBRICA CAVI - ANTENNE - ACCESSORI TV



CW7

WARNING CABLE

CEI-UNEL 36762 C-4 (U_o = 400 V)

Class CPR **E_{ca}**

CU


PLSF

Pet-sp

CU

LAP/SP

PLSF



	A	B	C	D	E	F
A	INNER CONDUCTOR		PLAIN COPPER			
B	INSULATION		LOW SMOKE AND FUME POLYVINYL-CHLORIDE			
C	NON-MIGRATING		SPIRAL POLYESTER TAPE			
D	DRAIN WIRE		PLAIN COPPER			
E	SHIELD		SPIRAL ALUMINIUM + POLYESTER TAPE			
			COVERAGE 100%			
F	SHEATH		LOW SMOKE AND FUME POLYVINYL-CHLORIDE			
	- PRINTING					

SIVA CAVO ALLARME SECTION MM² CEI-UNEL 36762
C-4 (U_o = 400 V) MADE IN ITALY CE 62 SETT/ANNO
EN 50575:2014 + A1:2016 E_{ca}

TEMPERATURE RANGE -25°C / +80°C

MECHANICAL DATA

	CONSTRUCTION	SECTION	SHEATH		WEIGHT KG/KM TOTAL
CW 0222.7	2 x (7 x 0,15 mm)	2 x 0,22 mm ²	ø 4,80 ± 0,20 mm	White - RAL 9003	30,6
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 0422.7	4 x (7 x 0,15 mm)	4 x 0,22 mm ²	ø 5,50 ± 0,20 mm	White - RAL 9003	36,7
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 0622.7	6 x (7 x 0,15 mm)	6 x 0,22 mm ²	ø 6,00 ± 0,20 mm	White - RAL 9003	42,4
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 0822.7	8 x (7 x 0,15 mm)	8 x 0,22 mm ²	ø 6,60 ± 0,20 mm	White - RAL 9003	48,4
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 1022.7	10 x (7 x 0,15 mm)	10 x 0,22 mm ²	ø 7,40 ± 0,20 mm	White - RAL 9003	54,7
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 1222.7	12 x (7 x 0,15 mm)	12 x 0,22 mm ²	ø 8,00 ± 0,20 mm	White - RAL 9003	60,4
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			
CW 1422.7	14 x (7 x 0,15 mm)	14 x 0,22 mm ²	ø 8,80 ± 0,20 mm	White - RAL 9003	65,1
	2 x (24 x 0,15 mm)	2 x 0,75 mm ²			

ELECTRICAL PROPERTIES at 20°C

CW7	VOLTAGE		CORES RESISTANCE		MIN. RESISTANCE INSULATION
	OPERATING	TEST	0,22 mm ²	0,50 mm ²	
	150 V	2000 V	140 Ohm/Km	40 Ohm/Km	200 MOhm/Km

The producer reserves himself to make modification on the item without any notice.